

# 8155

1/2 HP AC BELT DRIVE GARAGE DOOR OPENER



## Dependable Performance

### Connectivity

- **MyQ® Technology** enables you to securely monitor and control your garage door opener and houselights with your smartphone, tablet or computer.
- **Alerts** can be received as email or pop-up (push) notifications on your mobile device so that you always know the status of your garage door and houselights.
- **MyQ mobile app** is a free download requiring no activation or subscription fees.

### Performance

- **P3™ Motors** from LiftMaster® are reliable, durable and powerful – designed specifically for your needs.
- **1/2 HP AC motor** with belt drive provides reliable and maintenance free performance.
- **Energy-efficient** operation consumes up to 75% less power in standby mode.
- **4-year motor** warranty, 10-year belt warranty, and 1-year parts warranty.

### Safety and Security

- **Security+ 2.0™** safeguards your household – with every click a new code is sent to the garage door opener so that the door opens only for you.
- **PosiLock®** locks down your garage door by electronically monitoring against a forced opening.
- **Alert-2-Close** warning system provides audible and visual warnings when the garage door is about to close when using MyQ Technology.
- **The Protector System®** has safety sensors that project a light beam across the garage door opening, automatically reversing the door if anything interrupts the beam.

### Included Accessories:



#### 1-Button Remote Control (891LM)

Allows you to control a single garage door opener, gate operator or MyQ Light Accessory. With Security+ 2.0™, you are assured of a new code with every use.



#### Multi-Function Control Panel (882LM)

Allows you to program remote controls, keypads and MyQ Light Accessories from the control panel. Includes lockout remote controls for added security.

### Optional Accessories:



#### Internet Gateway (828LM)

Connect your MyQ-Enabled Garage Door Opener and Accessories to the Internet with this device and the free MyQ app.



#### Ceiling Mount (195LM)

Give your garage the style it's been missing by hiding the wires and cords with this sleek ceiling mount. Works in most standard garages.



#### Remote Light Control (825LM)

Allows you to control any lamp with your garage door opener remote control or smartphone via the Internet Gateway and the free MyQ app.



#### Door and Gate Monitor (829LM)

Enables you to monitor and close up to four garage doors or gates from any room in your house.

### SPEC SHEET STANDARD SPECIFICATIONS

#### DIMENSIONS

Installed Length: 124"  
Maximum Door Opening: 7' 6"  
Headroom Clearance Required: 2"  
\*Up to 10' with optional 8' or 10' rails

#### CARTONS

Number of Cartons: 2  
Carton 1: Dimensions and Contents:  
- 20" x 12" x 10"  
- 882LM Multi-Function Control Panel  
- 891LM 1-Button Remote Control  
- Garage Door Opener Head  
- The Protector System®  
Carton 2: Dimensions and Contents:  
- 10' 4" x 5" x 5"  
- Assembled Solid-Steel T-Rail

#### SECURITY+ 2.0™ RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light  
891LM 1-Button Remote Control  
Operating Range: 200' (approximately)  
Operating Temperature: -40°F to 150°F  
Battery (remote control): 3-Volt Lithium  
Frequency:  
- Remote Control: 310, 315, & 390 MHz Tri-Band  
- Receiver: Frequency Agile on 310, 315, & 390 MHz  
Security+ 2.0™ Anti-Burglary Coding

#### CONVENIENCE / SAFETY

PosiLock®  
Alert-2-Close  
Emergency/Quick Release  
Automatic Trolley Reconnect  
Ventilation/Pet Opening  
Down Safety Reverse  
Up Safety Stop  
Door Open/Beam Obstructed/Lights On  
The Protector System®  
Maintenance Alert System

### ELECTRICAL SPECIFICATIONS

#### POWER

Voltage: 120V AC, 60Hz  
Current Rating: 6.0A  
UL Listings: Yes  
Length of Line Cord: 4' (3-prong)

#### ENERGY EFFICIENCY

Approximately 1 Watt Power in Standby Mode\*  
Enhanced CFL (Compact Fluorescent) Compatible  
\*Standby Mode at down limit, work lights off

#### LOGIC TYPE

Solid-State Microcontroller with Built-in Surge Suppressor

#### LIGHTING

Number of Bulbs: 1  
Maximum Wattage: 100  
Length of Light Delay: 4 1/2 Minutes  
Type of Light Delay: Solid-State  
Enhanced CFL (Compact Fluorescent) Compatible, Max 26 Watts

### MECHANICAL SPECIFICATIONS

#### MOTOR

Horsepower: 1/2  
RPM: 1,625  
Thermal Protection: Automatic  
Lubrication: Permanent

#### DRIVE MECHANISM

Drive Means: Full Reinforced Drive Belt  
Reduction Means: Gear 16:1  
Door Linkage: Adjustable Door Arm

#### ADJUSTMENTS

Force: Electronic/Internal Auto Force  
Limit: Internal Electronic

#### TRAVEL RATE

Approximately 7"/Second

#### SHIPPING WEIGHTS

Head: 22 lbs.  
Rail: Belt—17 lbs.

#### MATERIALS

Chassis: Steel  
Rail: Solid-Steel T  
Trolley: Steel

#### WARRANTY

10 Year Belt Warranty  
4 Year Motor Warranty  
1 Year Parts Warranty

HOMELINK® Compatible (version 4.0 or higher)\*

\*May require an external adapter depending on the model and year of your vehicle.  
Visit [homelink.com](http://homelink.com) for additional information.